

Appl. No. 10/748,315  
Amdt. Dated Sep. 28, 2005  
Reply to Office Action of June 30, 2005

**Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (original): A surface lighting device for a display device, comprising:

- a light guide plate having a light incident surface;
  - a point light source opposite to the light incident surface; and
  - a micro-lens located between the point light source and the light incident surface, for collimating divergent rays emitted from the point light source into parallel rays;
- wherein the light guide plate and the point light source are placed at respective working distances from the micro-lens, whereby the divergent rays emitted from the point light source are coupled into the light incident surface via the micro-lens.

Claim 2 (original): The surface lighting device as described in claim 1, wherein the micro-lens has a superconic cross-section.

Claim 3 (currently amended): The surface lighting device as described in claim ~~[[1]]~~ 2, wherein the micro-lens comprises a plane surface facing the point light source and a convex surface opposite to the light incident surface.

Claim 4 (original): The surface lighting device as described in claim 1, wherein the micro-lens comprises a concave surface facing the point light source and a convex surface opposite to the light incident surface.

Appl. No. 10/748,315  
Amdt. Dated Sep. 28, 2005  
Reply to Office Action of June 30, 2005

**Claim 5 (original):** The surface lighting device as described in claim 1, wherein the point light source is a light emitting diode or a miniature bulb.

**Claim 6 (original):** The surface lighting device as described in claim 1, wherein the light guide plate is parallelepiped-shaped, wedge-shaped, or has a triangular profile.

**Claim 7 (currently amended):** The surface lighting device as described in claim 1, wherein the light guide plate further comprises a light output surface adjoining ~~[[to]]~~ the light incident surface, and a bottom surface opposite to the light ~~incident~~ output surface.

**Claim 8 (original):** The surface lighting device as described in claim 7, wherein the bottom surface has a dot pattern thereon, or has a plurality of v-cut grooves therein.

**Claim 9 (original):** The surface lighting device as described in claim 7, wherein the light incident surface has an anti-reflective film thereon.

**Claim 10 (currently amended):** A liquid crystal display device comprising:

- a liquid crystal panel; and
- a surface lighting device arranged under the liquid crystal panel for illuminating the liquid crystal panel, the surface lighting device comprising:
  - point light sources for emitting light beams;
  - a light guide plate having a light ~~[[input]]~~ incident surface for receiving the light beams and a light output surface for emitting the light beams; and

Appl. No. 10/748,315  
Amdt. Dated Sep. 28, 2005  
Reply to Office Action of June 30, 2005

micro-lenses for coupling the light beams from the point light sources into the light incident surface;

wherein the micro-lenses are positioned between the point light sources and the light incident surface, and the light beams emitted from the point light sources are coupled into the light incident surface via the micro-lenses.

Claim 11 (original): The liquid crystal display device as claimed in claim 10, wherein the micro-lenses collimate the light beams from the point light sources such that the light beams coupled into the light incident surface are substantially parallel.

Claim 12 (original): The liquid crystal display device as claimed in claim 10, wherein each of the micro-lenses has a superconic cross-section.

Claim 13 (currently amended): The liquid crystal display device as claimed in claim [[10]] 12, wherein each of the micro-lenses comprises a plane surface facing the point light source and a convex surface opposite to the light incident surface.

Claim 14 (original): The liquid crystal display device as claimed in claim 10, wherein each of the micro-lenses comprises a concave surface facing the point light source and a convex surface opposite to the light incident surface.

Claim 15 (original): A surface lighting device for a display device, comprising:

a light guide plate having a light incident surface;  
at least one light source opposite to the light incident surface; and  
a lens located between the light source and the light incident surface,  
for collimating divergent rays emitted from the light source into

Appl. No. 10/748,315  
Amdt. Dated Sep. 28, 2005  
Reply to Office Action of June 30, 2005

non-divergent rays;

wherein the light guide plate and the point light source are placed at respective working distances from the lens, whereby the divergent rays emitted from the light source are coupled into the light incident surface via the lens.

Claim 16 (currently amended): The light surface lighting device as described in claim 15, wherein said coupled non-divergent rays are essentially ~~in a parallel manner~~ to each other.

Claim 17 (currently amended): The light surface lighting device as described in claim 16, wherein ~~said the parallel rays in the parallel manner~~ are perpendicular to ~~said the~~ light incident surface.